

## Part I – General

### 1.1 Scope

A. Furnish plaques and hardware necessary to install wayfinding metal plaques shown on drawings and herein specified.

### 1.2 Submittals

A. Manufacturer's illustrated product literature and specifications.

B. Installation instructions

### 1.3 Quality Assurance

A. Manufacturer to have a minimum of 10 years experience in manufacturing wayfinding plaques.

B. All wayfinding plaques to be manufactured by one manufacturer.

## Part II – Products

### 2.1 Acceptable Manufacturer or Manufacturer's Representative

A. Gemini Incorporated

103 Mensing Way

Cannon Falls, MN 55009

Phone: 877-877-2922 or 507-263-3957

Fax: 800-627-8547 or 507-263-4887

Email: sales@geminiplaques.com

Web: www.geminiplaques.com

### 2.2 Materials (Metal Alloy Options)

A. Bronze (220 Commercial)

B. Aluminum (#5052)

C. Brass (C46400)

### 2.3 Process

1. Typical Wayfinding plaques with raised copy up to 24" x 24". Full color Giclee up to 48"x96".

2. Most Wayfinding are 1/8" thick. Thicker materials available upon request.

3. Edges — Single Line, Double Line, Inset Single Line, Inset Double Line and No Border are standard.

4. ADA\* with raised copy, emblems and Braille are integral to the body of the wayfinding plaque (one-piece construction)

a. Sand, Leatherette, Pebble and Stipple

b. Patina (Verde, Turquoise & Parrot Green), Oxidized (Dark Oxidized & Light Oxidized)

5. Background Colors

a. Standard: Black, Dark Oxide, Duranodic Bronze and Brown

b. Custom: 45 Gemini Baked Enamel colors as well as color-matching

6. Surface Finishes — stroke sanding is standard. Painted and Printed finishes are also available.

7. Wayfinding plaques are clear-coated and oven-baked with a two-part hardened seal of clear acrylic polyurethane.

### 2.4 Mounting Hardware

A. Hardware and instructions are provided for several mounting methods, including Blind Mount, Double-Face Tape, Solid Wall Mount, Hollow Wall Mount, Wood Wall Mount, Garden Stake Mount and Square Post Mount.

### 2.5 Manufacture

A. Wayfinding plaques shall be made of either Bronze (220 Commercial) Aluminum (#5052) or Brass (C46400).

B. Wayfinding plaques shall use \_\_\_\_\_ letterstyle with letters that are \_\_\_\_ inches high, as indicated on the drawings.

C. Mounting shall be \_\_\_\_\_

## Part III – Execution

### 3.1 Installation

A. A qualified installer shall install Wayfinding plaques. Additional structural support may be required for larger/heavier plaques.

### 3.2 Warranty

A. Wayfinding plaques shall be guaranteed for the life of the original installation.

### 3.3 Maintenance

A. Cleaning of Plaques as needed, per manufacturer's recommendations.